1 Machine Image



2 Machine Description

Wire Marking Hot Stamping for Wire_Cable Imprinting

Introduction

Wire Marking Hot Stamping for Wire_Cable Imprinting also name Wire rubber ironing machine and cable rubber stamping machine, wire printer Electric ironing machine, used for printing hot stamping in marking Wire, cable, Shrink Sleeve, Rubber/Plastic tube, is designed with 40pcs difference characters, including number: 0~9, Letters: A~Z, Symbol: . / + - and Blank, same as 0123456789ABCDEFGHIJKLMNOPQRSTUVWXYZ./+-, Machine is also capable of using engraved logo dies for customizing sleeving

Application

For hot stamping in marking/printing cable and wire insulation, heat shrink sleeve, and plastic tubing

Character

Less operator fatigue than a lever operated machine

Solid state dwell timer for better repeatability

Can Be Easily Interfaced With Wire Processing Machines

For hot stamping cable and wire insulation, heat shrink sleeving, and plastic tubing.

Stepper motor with electronic control ensures accurate, easy print interval markings

Wire can be pulled through by hand or using production machinery

Marks identification codes in virtually any print interval

Excellent throughput – 75 feet or 20 meters per minute with optional Automated Drive System

Single wire guide handles a range of wire diameters reducing setup time

Simple control and operation

10 flame hardened wheels, each with up to 40 characters allows for quick selection

of identification codes

Digital temperature control with feedback loop

Optional second tape carriage provides up to spool reduces production interruptions

Rugged, heavy duty construction for the production environment

Character Disk

Flat-faced Marking Discs

Flat-faced marking discs have flat-faced type. They are used for marking heat-shrink tubing and large diameter wires and cables.

Concave-faced Marking Discs

Wire marking discs have concave type. They are made in various character sizes to cover a range of wire diameters. Both vertical reading and horizontal reading characters are available.

Mainly parameter	
Power supply	220V/380V or under request
Operation temperature	100 degree
Wire and Cable Size	1.5mm~10mm
Number of Disks	7,9,11, 16, (bit), customized
Characters of Each Disk	A-Z, 0-9,.,/,+,-, space
Character size	1.5*1.5mm,1.8*1.8mm,2*2mm,2.4*2.4mm,3*3mm
Character Surface	Flat/Concave
Material	Rubber, PVC, Teflon
Operation Mode	Push Button or foot pedal
Foil	Any Color, 60meter and 120 meters
Net Weight	25kgs
Gross Weight	35kg
Dimensions	355 * 350 * 280mm

3 Machine Uses **№**





KEEPLEADER ADD:RONGXING BUILDING,BANTIAN,LONGGANG,SHENZHEN,CHINA
W.KEEPLEADER.COM TEL:00-86-755-84190358 EMAIL:SALES@KEEPLEADER.COM



